




SEGUE TABELLA - FOLLOW TABLE

ARTICOLO ARTICLE	MACCHINA MACHINE	POS. POS.	Ø A BARRA Ø A BAR	Ø D RULLO Ø D ROLLER	L	S	T	C	H
ART. 158.22.30									
WICKMAN									
158.10.22.30	5/8"	4-5	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
GILDEMEISTER									
158.11.22.30	AS 16 - GM 6	4-5	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
158.15.22.30	AS 20 - GS 20 - GM 20	4-5	mn Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
SCHÜTTE									
158.08.22.30	SF 13	4-5	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
158.21.22.30	SE 16 - SF 20	4-5	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
MORI SAY - EUROTURN									
158.14.22.30	6/20	4-5	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
INDEX									
158.13.22.30	MS 25	2-3-5	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
ART. 158.26.30									
WICKMAN									
158.20.26.30	1"	2-4-5	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
SCHÜTTE									
158.22.26.30	SE 25	4-5	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
158.46.26.30	SF 26	4-5	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
158.55.26.30	SF 26L	4-5	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
MORI SAY - EUROTURN									
158.24.26.30	6/25	4-5	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
INDEX									
158.13.26.30	MS 25	4-5	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2

A RICHIESTA ALTRE ATTREZZATURE/FURTHER EQUIPMENTS ON REQUEST

ARTICOLO ARTICLE	MACCHINA MACHINE	POS. POS.	Ø A BARRA Ø A BAR	Ø D RULLO Ø D ROLLER	L	S	T	C	H
ART. 158.34.30									
WICKMAN									
158.30.34.30	1" 3/8	2-4-5	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
GILDEMEISTER									
158.27.34.30	AA 32	4-5-6-7	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
158.31.34.30	AS 32	4-5	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
158.56.34.30	GM 32	4-5	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
SCHÜTTE									
158.33.34.30	SD 25 - SD 32	4-5	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
MORI SAY - EUROTURN									
158.24.34.30	6/32	4-5	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
158.53.34.30	8/32	4-5	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
INDEX									
158.61.34.30	KS 32	4-5	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
ART. 158.53.30									
WICKMAN									
158.30.53.30	1" 3/4	2-4-5	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
GILDEMEISTER									
158.32.53.30	AS 40 - AS 48	4-5	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
158.36.53.30	AA 48	4-5	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
158.47.53.30	GM 42	4-5	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
SCHÜTTE									
158.42.53.30	SD 50	4-5	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
158.48.53.30	AD 40	4-5	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
MORI SAY - EUROTURN									
158.28.53.30	6/42	4-5	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
INDEX									
158.35.53.30	KS 42	4-5	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
ART. 158.65.30									
WICKMAN									
158.40.65.30	2" 1/4	4-5	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
158.41.65.30	2" 5/8	4-5	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
158.50.65.30	3" 1/2	4-5	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
158.58.65.30	3" 1/4	4-5	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
GILDEMEISTER									
158.44.65.30	AS 55 - AS 67	4-5	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
158.51.65.30	AA 67	4-5	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
SCHÜTTE									
158.43.65.30	SD 63-80	4-5	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2