





POSIZIONE 3

POSITION 3



SEGUE TABELLA - FOLLOW TABLE

ARTICOLO ARTICLE	MACCHINA MACHINE	POS. POS.	Ø A BARRA Ø A BAR	Ø D RULLO Ø D ROLLER	L	S	T	C	H
ART. 158.22.40									
WICKMAN									
158.10.22.40	5/8"	3	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
GILDEMEISTER									
158.11.22.40	AS 16 - GM 6	3	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
158.15.22.40	AS 20 - GS 20 - GM 20	3	mn Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
SCHÜTTE									
158.08.22.40	SF 13	3	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
158.21.22.40	SE 16 - SF 20	3	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
MORI SAY - EUROTURN									
158.14.22.40	6/20	3	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
INDEX									
158.13.22.40	MS 25	3	min Ø 6 - max Ø 22	min Ø 22 - max Ø 28	23	20	3.5	20.5	20.5-A/2
ART. 158.26.40									
WICKMAN									
158.20.26.40	1"	3	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
SCHÜTTE									
158.22.26.40	SE 25	3	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
158.46.26.40	SF 26	3	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
158.55.26.40	SF 26L	3	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
MORI SAY - EUROTURN									
158.24.26.40	6/25	3	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2
INDEX									
158.13.26.40	MS 25	3	min Ø 6 - max Ø 26	min Ø 24 - max Ø 34	28	23	6.5	23	23-A/2

A RICHIESTA ALTRE ATTREZZATURE/FURTHER EQUIPMENTS ON REQUEST

ARTICOLO ARTICLE	MACCHINA MACHINE	POS. POS.	Ø A BARRA Ø A BAR	Ø D RULLO Ø D ROLLER	L	S	T	C	H
ART. 158.34.40									
WICKMAN									
158.30.34.40	1" 3/8	3	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
GILDEMEISTER									
158.27.34.40	AA 32	3	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
158.31.34.40	AS 32	3	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
158.56.34.40	GM 32	3	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
SCHÜTTE									
158.33.34.40	SD 25 - SD 32	3	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
MORI SAY - EUROTURN									
158.24.34.40	6/32	3	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
158.53.34.40	8/32	3	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
INDEX									
158.61.34.40	KS 32	3	min Ø 28 - max Ø 34	min Ø 26 - max Ø 32	40	34	9	33	33-A/2
ART. 158.53.30									
WICKMAN									
158.30.53.40	1" 3/4	3	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
GILDEMEISTER									
158.32.53.40	AS 40 - AS 48	3	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
158.36.53.40	AA 48	3	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
158.47.53.40	GM 42	3	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
SCHÜTTE									
158.42.53.40	SD 50	3	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
158.48.53.40	AD 40	3	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
MORI SAY - EUROTURN									
158.28.53.40	6/42	3	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
INDEX									
158.35.53.40	KS 42	3	min Ø 26 - max Ø 53	min Ø 28 - max Ø 32	40	34	9	43	43-A/2
ART. 158.65.40									
WICKMAN									
158.40.65.40	2" 1/4	3	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
158.41.65.40	2" 5/8	3	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
158.50.65.40	3" 1/2	3	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
158.58.65.40	3" 1/4	3	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
GILDEMEISTER									
158.44.65.40	AS 55 - AS 67	3	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
158.51.65.40	AA 67	3	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2
SCHÜTTE									
158.43.65.40	SD 63-80	3	min Ø 30 - max Ø 65	min Ø 28 - max Ø 42	50	45	12	63	63-A/2